

EZ-Flo Continuous Weigh Flow Scale Prices -5-1-06

800-372-7731 952-939-6000 FAX 952-939-1026

e mail clarence@clarencerichard.com web www.clarencerichard.com

Flow Scale up to 40 TPH (8" square vertical tube @ 80LBs/cubic Foot)

Flow Scale up to 60 TPH (10" square vertical tube @ 80LBs/cubic Foot)

*(size to be determined when completing Application Data Sheet)

** All flow scales to include Integrator with Rate Indicator and Totalizer as pictured here.



Remote Control on table-

2', 2.25', 2.5' ... 8" tube Flow Scale

3.5' 10" tube Flow Scale

8" tube Divert Chute (Calibration Bypass)

10" tube Divert Chute (pictured above)

Options

*High Temp Compensation for hot aggregate dust..\$

*Integrator 4-20 ma output Rate signal

*Integrator - Batch Control Relay Input/Output

*Calibration Gate.. 10" or 12" Auger Slide Gate. (saddle from slide gate to auger not included)
or

*Calibration 8" tube Divert Chute

*Calibration 10" tube Divert Chute \$

*Material Calibration Scale to calibrate flow scale- ½ Lb. resolution

DIGITAL SCALE

12 1/2"L x 11 3/4"W Steel Platform



*Transition--Square to Round -- 8" Scale to 7" Hose Transition -
10" Scale to 8" Hose Transition -

Load Cell Cable, rugged jacket, stranded, cut to length over 100'.

Remote Control with Automatic/Manual Blending and Startup .. Sloped 12" Table Top Control Panel \$3950.



Option:

- * Control Power - Quick Disconnect – with 100' - SO Jacket with PVC insulated 19 conductor - control cable
- * For digital frequency remote setpoint input (in lieu of standard 4-20ma input) usually taken from Asphalt flow Meter -.
- * Variable Frequency Drive with Motor – Near Zero to 200% speed. \$____ dependant on application
- Custom Controls \$____ dependant on application